

Track light SFL series 36W GS-TL36WLC77




Product parameter

- LED power : 32.4W(36vDC 900mA)
- Lamp consumption : 36W
- Adapter : 3 phase(4-wire, 6-wire)
- Input voltage : 200-240vAC
- UGR : (Lens 12-15)(Reflector 15-19)
- Size : φ77*L170mm
- Life span : 50,000 hrs
- Warranty : 5 years
- Beam angle : (Lens15°/24°/36°/60°)(Reflector: 30°/40°/60°)




Dimmable



Datasheet

Part No.	COB brand	CCT	Output			Beam angle
			CRI80	CRI90	CRI96	
GS-TL36WLC77B	Bridgelux V13C	2700K-7000K single color	3700-4200lm	3400-3800lm	3200-3400lm	Reflector 30°/40°/60° Lens 15°/24°/36°/60°
GS-TL36WLC77H	CITIZEN1208H		no	4200-4600lm	no	
GS-TL36WLC77C	CITIZEN1206		3700-4200lm	3400-3800lm	3200-3400lm	
GS-TL36WLC77TP	TYANSHINE	3000k/4000k/5700k	no	2500-3200lm	no	
GS-TL36WLC77TC		2700k~5700k tunable				

Packing



Installation Instuction Warning: Make sure that the power on the track rail is off before installation.

1. Fix the track rails on the suspended ceiling
2. Make the power adaptor set to OFF
3. Embed the track light on the track rails
4. Turn the handle 90° degrees according to the direction as shown in the left picture, make sure the adaptor be locked in the track rails